

## Pump Chamber 250 Litre WP250

Domestic/Commercial packaged pump station

### APPLICATION

Wallace WP250 is designed as a secondary unit for domestic applications where a dwelling is below conventional council sewer line and a storage type pump station is required with limited space availability

### DESIGN FEATURES

- Moulded PE tank has compact overall size of 710mm diametre X 780mm (Overall height Incl lid 870mm) with approximate volume of 250ltr
- Compact design can be installed in confined space.
- Unit can be installed Above-Ground or Under-Ground.
- Gland design allows easy access and removal of separate float switches(if supplied) without disturbing pump and piping.
- Package supplied complete with selected Pump.
- Control panel **MUST** be installed in weatherproof location.
- Package can be supplied with High Level Alarm System with or without auto water shutoff via solenoid valves. Alarm panel **MUST** be installed in weatherproof location.
- Non Return Valve, Isolating valve and union supplied assembled with 100mm PVC inlet and 50mm PVC outlet



### TECHNICAL DATA

|                      |                          |              |                             |
|----------------------|--------------------------|--------------|-----------------------------|
| Tank Volume (Litres) | 250                      | Alarm (Type) | Pump Dependant              |
| Dimensions (mm)      | 710 $\varnothing$ x 780H | Inlet        | 100mm UPVC                  |
| Total Weight (Kg)    | 30                       | Discharge    | 50mm PVC class D            |
| Pump (Type)          | Application Specific     | Valves       | 50mm non return & isolating |

Pump Performance Based on W-750SK

