

DLM Wallace

Chemwatch: 20994 Version No: 6.1

Safety Data Sheet according to the Health and Safety at Work (Hazardous Substances) Regulations 2017

Chemwatch Hazard Alert Code: 4

Issue Date: 23/12/2022 Print Date: 16/10/2024 S.GHS.NZL.EN.E

SECTION 1 Identification of the substance / mixture and of the company / undertaking

Product Identifier	
CA 801 Soldering Fluid	
Not Applicable	
soldering flux; brazing flux; WIS 801 brazing flux; flux WIS801; Eziweld flux; Ezi-Weld 801 Fluid	
CORROSIVE LIQUID, N.O.S. (contains hydrochloric acid)	
Not Applicable	
Not Available	

Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses	Brazing/soldering flux.
--------------------------	-------------------------

Details of the manufacturer or supplier of the safety data sheet

Registered company name	DLM Wallace	
Address	55 Maurice Road, Penrose Auckland 1061 New Zealand	
Telephone	+64 9 622 9100	
Fax	+64 9 622 9119	
Website	site www.dlmwallace.co.nz	
Email	enquiries@dlmwallace.co.nz	

Emergency telephone number

Association / Organisation	National Poisons Centre
Emergency telephone number(s)	0800 764 766
Other emergency telephone number(s)	Not Available

SECTION 2 Hazards identification

Classification of the substance or mixture

Classification [1]	Acute Toxicity (Oral) Category 4, Skin Corrosion/Irritation Category 1A, Serious Eye Damage/Eye Irritation Category 1, Acute Toxicity (Inhalation) Category 3, Hazardous to the Aquatic Environment Acute Hazard Category 1, Hazardous to the Aquatic Environment Long-Term Hazard Category 1, Hazardous to Terrestrial Vertebrates
Legend:	1. Classified by Chemwatch; 2. Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex VI
Determined by Chemwatch using GHS/HSNO criteria	6.1C (inhalation), 6.1D (oral), 8.2A, 8.3A, 9.1A, 9.3B

Label elements

Hazard pictogram(s)







Signal word Danger

Hazard statement(s)

H302	Harmful if swallowed.	
H314	Causes severe skin burns and eye damage.	
H331	Toxic if inhaled.	
H410	Very toxic to aquatic life with long lasting effects.	
H432	Hazardous to terrestrial vertebrates.	

Chemwatch: 20994 Page 2 of 11

CA 801 Soldering Fluid

Issue Date: 23/12/2022 Print Date: 16/10/2024

Precautionary statement(s) Prevention

Version No: 6.1

P260	Do not breathe mist/vapours/spray.	
P264	Wash all exposed external body areas thoroughly after handling.	
P271	Use only outdoors or in a well-ventilated area.	
P280	Wear protective gloves, protective clothing, eye protection and face protection.	
P270	Do not eat, drink or smoke when using this product.	
P273	Avoid release to the environment.	

Precautionary statement(s) Response

P301+P330+P331	IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. If more than 15 mins from Doctor, INDUCE VOMITING (if conscious).	
P303+P361+P353	IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water [or shower].	
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.	
P310	Immediately call a POISON CENTER/doctor/physician/first aider.	
P363	Wash contaminated clothing before reuse.	
P304+P340	IF INHALED: Remove person to fresh air and keep comfortable for breathing.	
P391	P391 Collect spillage.	

Precautionary statement(s) Storage

• • • • • • • • • • • • • • • • • • • •		
P403+P233	Store in a well-ventilated place. Keep container tightly closed.	
P405	Store locked up.	

Precautionary statement(s) Disposal

P501 Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

SECTION 3 Composition / information on ingredients

Substances

See section below for composition of Mixtures

Mixtures

CAS No	%[weight]	Name
7646-85-7	10-30	zinc chloride
7647-01-0	<10	hydrochloric acid
Not Available	>60	Ingredients determined not to be hazardous
Legend:	Classified by Chemwatch; 2. 0 VI; 4. Classification drawn from 0	Classification drawn from CCID EPA NZ; 3. Classification drawn from Regulation (EU) No 1272/2008 - Annex C&L * EU IOELVs available

SECTION 4 First aid measures

C

Description of first aid measur	es			
Eye Contact	If this product comes in contact with the eyes: Immediately hold eyelids apart and flush the eye continuously with running water. Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids. Continue flushing until advised to stop by the Poisons Information Centre or a doctor, or for at least 15 minutes. Transport to hospital or doctor without delay. Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.			
Skin Contact	If skin or hair contact occurs: Immediately flush body and clothes with large amounts of water, using safety shower if available. Quickly remove all contaminated clothing, including footwear. Wash skin and hair with running water. Continue flushing with water until advised to stop by the Poisons Information Centre. Transport to hospital, or doctor.			
Inhalation	 If fumes or combustion products are inhaled remove from contaminated area. Lay patient down. Keep warm and rested. Prostheses such as false teeth, which may block airway, should be removed, where possible, prior to initiating first aid procedures. Apply artificial respiration if not breathing, preferably with a demand valve resuscitator, bag-valve mask device, or pocket mask as trained. Perform CPR if necessary. Transport to hospital, or doctor, without delay. Inhalation of vapours or aerosols (mists, fumes) may cause lung oedema. Corrosive substances may cause lung damage (e.g. lung oedema, fluid in the lungs). As this reaction may be delayed up to 24 hours after exposure, affected individuals need complete rest (preferably in semi-recumbent posture) and must be kept under medical observation even if no symptoms are (yet) manifested. Before any such manifestation, the administration of a spray containing a dexamethasone derivative or beclomethasone derivative may be considered. This must definitely be left to a doctor or person authorised by him/her. (ICSC13719) 			
Ingestion	 For advice, contact a Poisons Information Centre or a doctor at once. Urgent hospital treatment is likely to be needed. If swallowed do NOT induce vomiting. If vomiting occurs, lean patient forward or place on left side (head-down position, if possible) to maintain open airway and prevent aspiration. 			

Never give liquid to a person showing signs of being sleepy or with reduced awareness; i.e. becoming unconscious.
 Give water to rinse out mouth, then provide liquid slowly and as much as casualty can comfortably drink.

Chemwatch: 20994 Page 3 of 11

CA 801 Soldering Fluid

Issue Date: 23/12/2022 Print Date: 16/10/2024

Transport to hospital or doctor without delay.

Indication of any immediate medical attention and special treatment needed

For acute or short term repeated exposures to strong acids:

- Airway problems may arise from laryngeal edema and inhalation exposure. Treat with 100% oxygen initially.
- Respiratory distress may require cricothyroidotomy if endotracheal intubation is contraindicated by excessive swelling
- Intravenous lines should be established immediately in all cases where there is evidence of circulatory compromise.
- Strong acids produce a coagulation necrosis characterised by formation of a coagulum (eschar) as a result of the dessicating action of the acid on proteins in specific tissues

INGESTION:

Version No: 6.1

- Immediate dilution (milk or water) within 30 minutes post ingestion is recommended.
- DO NOT attempt to neutralise the acid since exothermic reaction may extend the corrosive injury
- ▶ Be careful to avoid further vomit since re-exposure of the mucosa to the acid is harmful. Limit fluids to one or two glasses in an adult.
- Charcoal has no place in acid management.
- Some authors suggest the use of lavage within 1 hour of ingestion.

SKIN:

- Skin lesions require copious saline irrigation. Treat chemical burns as thermal burns with non-adherent gauze and wrapping.
- Deep second-degree burns may benefit from topical silver sulfadiazine.

EYE:

- Eye injuries require retraction of the eyelids to ensure thorough irrigation of the conjuctival cul-de-sacs. Irrigation should last at least 20-30 minutes. DO NOT use neutralising agents or any other additives. Several litres of saline are required.
- Cycloplegic drops, (1% cyclopentolate for short-term use or 5% homatropine for longer term use) antibiotic drops, vasoconstrictive agents or artificial tears may be indicated dependent on the severity of the injury.
- Steroid eye drops should only be administered with the approval of a consulting ophthalmologist).

[Ellenhorn and Barceloux: Medical Toxicology]

- Absorption of zinc compounds occurs in the small intestine.
- ▶ The metal is heavily protein bound.
- · Elimination results primarily from faecal excretion
- The usual measures for decontamination (Ipecac Syrup, lavage, charcoal or cathartics) may be administered, although patients usually have sufficient vomiting not to require them
- CaNa2EDTA has been used successfully to normalise zinc levels and is the agent of choice.

[Ellenhorn and Barceloux: Medical Toxicology]

SECTION 5 Firefighting measures

Extinguishing media

- Water spray or fog.
- Foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

Special hazards arising from the substrate or mixture

Fire Incompatibility None known

Advice for firefighters

Alert Fire Brigade and tell them location and nature of hazard.
Wear full body protective clothing with breathing apparatus

- ▶ Prevent, by any means available, spillage from entering drains or water course.
- Use fire fighting procedures suitable for surrounding area. Fire Fighting
 - Do not approach containers suspected to be hot
 - ▶ Cool fire exposed containers with water spray from a protected location.
 - If safe to do so, remove containers from path of fire.

Fire/Explosion Hazard

- Non combustible. Not considered to be a significant fire risk.
- Acids may react with metals to produce hydrogen, a highly flammable and explosive gas.
- Heating may cause expansion or decomposition leading to violent rupture of containers. May emit corrosive, poisonous fumes. May emit acrid smoke.

Decomposition may produce toxic fumes of:

hydrogen chloride

metal oxides

SECTION 6 Accidental release measures

Personal precautions, protective equipment and emergency procedures

See section 8

Environmental precautions

See section 12

Methods and material for containment and cleaning up

 Drains for storage or use areas should have retention basins for pH adjustments and dilution of spills before discharge or disposal of
material.
▶ Check regularly for spills and leaks.

Minor Spills

- Clean up all spills immediately.
- Avoid breathing vapours and contact with skin and eyes.
- Control personal contact with the substance, by using protective equipment.
- Contain and absorb spill with sand, earth, inert material or vermiculite.
- Wipe up.
- Place in a suitable, labelled container for waste disposal

Major Spills

- Clear area of personnel and move upwind.
- Alert Fire Brigade and tell them location and nature of hazard.
- Wear full body protective clothing with breathing apparatus

Chemwatch: **20994** Page **4** of **11**

CA 801 Soldering Fluid

Issue Date: 23/12/2022 Print Date: 16/10/2024

- Prevent, by any means available, spillage from entering drains or water course.
- ► Consider evacuation (or protect in place).
- Stop leak if safe to do so.
- Contain spill with sand, earth or vermiculite.

Personal Protective Equipment advice is contained in Section 8 of the SDS.

SECTION 7 Handling and storage

Precautions for safe handling

Version No: 6.1

▶ DO NOT allow clothing wet with material to stay in contact with skin

- Avoid all personal contact, including inhalation.
- Wear protective clothing when risk of exposure occurs.

Safe handling Use in a well-ventilated area.

- ▶ WARNING: To avoid violent reaction, ALWAYS add material to water and NEVER water to material.
- Avoid smoking, naked lights or ignition sources.
- Avoid contact with incompatible materials.
- When handling, DO NOT eat, drink or smoke.

Other information

- Store in original containers.
- Keep containers securely sealed.

 Store in a cool, dry, well-ventilated area.
- Store away from incompatible materials and foodstuff containers.
- Protect containers against physical damage and check regularly for leaks.
- ▶ Observe manufacturer's storage and handling recommendations contained within this SDS.

Conditions for safe storage, including any incompatibilities

- ▶ DO NOT use aluminium or galvanised containers
- Check regularly for spills and leaks
- Lined metal can, lined metal pail/ can.
- Plastic pail.
- Polyliner drum.
- Prolymier dram.
- Packing as recommended by manufacturer.
- Check all containers are clearly labelled and free from leaks.

For low viscosity materials

Suitable container

- Drums and jerricans must be of the non-removable head type.
- ▶ Where a can is to be used as an inner package, the can must have a screwed enclosure.

For materials with a viscosity of at least 2680 cSt. (23 deg. C) and solids (between 15 C deg. and 40 deg C.):

- Removable head packaging;
- ▶ Cans with friction closures and
- low pressure tubes and cartridges

may be used.

Where combination packages are used, and the inner packages are of glass, porcelain or stoneware, there must be sufficient inert cushioning material in contact with inner and outer packages unless the outer packaging is a close fitting moulded plastic box and the substances are not incompatible with the plastic.

Storage incompatibility

- ▶ Inorganic acids are generally soluble in water with the release of hydrogen ions. The resulting solutions have pH's of less than 7.0.
- Inorganic acids neutralise chemical bases (for example: amines and inorganic hydroxides) to form salts neutralisation can generate dangerously large amounts of heat in small spaces.
- The dissolution of inorganic acids in water or the dilution of their concentrated solutions with additional water may generate significant heat.
- ▶ The addition of water to inorganic acids often generates sufficient heat in the small region of mixing to cause some of the water to boil explosively. The resulting "bumping" can spatter the acid.
- Inorganic acids react with active metals, including such structural metals as aluminum and iron, to release hydrogen, a flammable gas.

SECTION 8 Exposure controls / personal protection

Control parameters

Occupational Exposure Limits (OEL)

INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
New Zealand Workplace Exposure Standards (WES)	zinc chloride	Zinc chloride fume	1 mg/m3	2 mg/m3	Not Available	Not Available
New Zealand Workplace Exposure Standards (WES)	hydrochloric acid	Hydrogen chloride	Not Available	Not Available	5 ppm / 7.5 mg/m3	Not Available

Ingredient	Original IDLH	Revised IDLH
zinc chloride	50 mg/m3	Not Available
hydrochloric acid	50 ppm	Not Available

Exposure controls

Appropriate engineering controls


Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are:

Process controls which involve changing the way a job activity or process is done to reduce the risk.

Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment. Ventilation can remove or dilute an air contaminant if designed properly. The design of a ventilation system must match the particular process and chemical or contaminant in use.

Employers may need to use multiple types of controls to prevent employee overexposure.

Issue Date: 23/12/2022 Print Date: 16/10/2024



Version No: 6.1









Eye and face protection

- Safety glasses with unperforated side shields may be used where continuous eye protection is desirable, as in laboratories; spectacles are not sufficient where complete eye protection is needed such as when handling bulk-quantities, where there is a danger of splashing, or if the material may be under pressure
- Chemical goggles. Whenever there is a danger of the material coming in contact with the eyes; goggles must be properly fitted. [AS/NZS 1337.1, EN166 or national equivalent]
- Full face shield (20 cm, 8 in minimum) may be required for supplementary but never for primary protection of eyes; these afford face
- Alternatively a gas mask may replace splash goggles and face shields.
- Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task,

Skin protection

See Hand protection below

▶ Elbow length PVC gloves

▶ When handling corrosive liquids, wear trousers or overalls outside of boots, to avoid spills entering boots.

Hands/feet protection

The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application. The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed

when making a final choice.

Personal hygiene is a key element of effective hand care. Gloves must only be worn on clean hands. After using gloves, hands should be washed and dried thoroughly. Application of a non-perfumed moisturiser is recommended.

Body protection

See Other protection below

Other protection

- Overalls
- PVC Apron.
- PVC protective suit may be required if exposure severe.
- Evewash unit.
- Ensure there is ready access to a safety shower.

Recommended material(s)

GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following substance(s) are taken into account in the computergenerated selection:

CA 801 Soldering Fluid

Material	CPI
BUTYL	Α
BUTYL/NEOPRENE	Α
HYPALON	Α
NEOPRENE	Α
NEOPRENE/NATURAL	Α
NITRILE	A
NITRILE+PVC	A
PE/EVAL/PE	Α
PVC	Α
SARANEX-23	A
VITON/NEOPRENE	Α
NATURAL RUBBER	В
NATURAL+NEOPRENE	В
NAT+NEOPR+NITRILE	С

* CPI - Chemwatch Performance Index

- A: Best Selection
- B: Satisfactory: may degrade after 4 hours continuous immersion
- C: Poor to Dangerous Choice for other than short term immersion

NOTE: As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

* Where the glove is to be used on a short term, casual or infrequent basis, factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

Ansell Glove Selection

Glove — In order of recommendation
AlphaTec 02-100
AlphaTec® 15-554
AlphaTec® Solvex® 37-185
AlphaTec® 38-612
AlphaTec® 58-008
AlphaTec® 58-530B
AlphaTec® 58-530W

Respiratory protection

Type B-P Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required. Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor	Half-Face Respirator	Full-Face Respirator	Powered Air Respirator
up to 10 x ES	B-AUS P2	-	B-PAPR-AUS / Class 1 P2
up to 50 x ES	-	B-AUS / Class 1 P2	-
up to 100 x ES	-	B-2 P2	B-PAPR-2 P2 ^

^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

76b-p()

Chemwatch: 20994 Version No: 6.1

Page 6 of 11 CA 801 Soldering Fluid Issue Date: 23/12/2022 Print Date: 16/10/2024

AlphaTec® 58-735 AlphaTec® 79-700 AlphaTec® Solvex® 37-675

The suggested gloves for use should be confirmed with the glove supplier.

SECTION 9 Physical and chemical properties

Information on basic physical and chemical properties

	and chemical properties		
Appearance	Clear, corrosive liquid with sharp acidic odour; mi	xes with water.	
Physical state	Liquid	Relative density (Water = 1)	1.24
Odour	Not Available	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature (°C)	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available
Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Applicable
Flash point (°C)	Not Available	Taste	Not Available
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Not Available	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available
Heat of Combustion (kJ/g)	Not Available	Ignition Distance (cm)	Not Available
Flame Height (cm)	Not Available	Flame Duration (s)	Not Available
Enclosed Space Ignition Time Equivalent (s/m3)	Not Available	Enclosed Space Ignition Deflagration Density (g/m3)	Not Available

SECTION 10 Stability and reactivity

Reactivity	See section 7
Chemical stability	 Contact with alkaline material liberates heat Unstable in the presence of incompatible materials. Product is considered stable. Hazardous polymerisation will not occur.
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

SECTION 11 Toxicological information

Information on toxicological ef	fects
Inhaled	Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be harmful. The material can cause respiratory irritation in some persons. The body's response to such irritation can cause further lung damage. Corrosive acids can cause irritation of the respiratory tract, with coughing, choking and mucous membrane damage. There may be dizziness, headache, nausea and weakness. Hydrogen chloride (HCI) vapour or fumes present a hazard from a single acute exposure. Exposures of 1300 to 2000 ppm have been lethal to humans in a few minutes. Inhalation of HCI may cause choking, coughing, burning sensation and may cause ulceration of the nose, throat and larynx. Fluid on the lungs followed by generalised lung damage may follow. Breathing of HCI vapour may aggravate asthma and inflammatory or fibrotic pulmonary disease. High concentrations cause necrosis of the tracheal and bronchial epithelium, pulmonary oedema, atelectasis and emphysema and damage to the pulmonary blood vessels and liver. Welding or flame cutting of metals with zinc or zinc dust coatings may result in inhalation of zinc oxide fume; high concentrations of zinc oxide fume may result in "metal fume fever"; also known as "brass chills", an industrial disease of short duration. [I.L.O] Symptoms include malaise, fever, weakness, nausea and may appear quickly if operations occur in enclosed or poorly ventilated areas.
Ingestion	Accidental ingestion of the material may be harmful; animal experiments indicate that ingestion of less than 150 gram may be fatal or may produce serious damage to the health of the individual. Ingestion of acidic corrosives may produce burns around and in the mouth, the throat and oesophagus. Immediate pain and difficulties in swallowing and speaking may also be evident.
Skin Contact	Skin contact with acidic corrosives may result in pain and burns; these may be deep with distinct edges and may heal slowly with the formation of scar tissue. Open cuts, abraded or irritated skin should not be exposed to this material Entry into the blood-stream, through, for example, cuts, abrasions or lesions, may produce systemic injury with harmful effects. Examine the skin prior to the use of the material and ensure that any external damage is suitably protected.

Page **7** of **11** Issue Date: 23/12/2022 Print Date: 16/10/2024

Eye	If applied to the eyes, this material causes severe eye damage. Direct eye contact with acid corrosives may produce pain, tears, sensitivity to light and burns. Mild burns of the epithelia generally recover rapidly and completely.			
Chronic	Repeated or prolonged exposure to acids may result in the erosion of to lung, with cough, and inflammation of lung tissue often occurs. There has been some concern that this material can cause cancer or m Substance accumulation, in the human body, may occur and may caus exposure. Chronic minor exposure to hydrogen chloride (HCI) vapour or fume may and gums; and ulceration of the mucous membranes of the nose. Work and a number of cases of chronic bronchitis (airway inflammation) have solutions of hydrogen chloride may cause skin inflammation. Welding or flame cutting of metals with zinc or zinc dust coatings may roxide fume may result in "metal fume fever"; also known as "brass chill malaise, fever, weakness, nausea and may appear quickly if operations.	nutations but there is e some concern following cause discolouraters exposed to hyde also been reporter esult in inhalation of s", an industrial discontinuation of the control of the con	is not enough data to make an assessment. Illowing repeated or long-term occupational Ition or erosion of the teeth, bleeding of the nose Irrochloric acid suffered from stomach inflammation If Repeated or prolonged exposure to dilute If zinc oxide fume; high concentrations of zinc Incease of short duration. [I.L.O] Symptoms include	
	TOXICITY	IRRITATION		
CA 801 Soldering Fluid	Not Available	Not Available		
	TOXICITY	IRRITATION		
zinc chloride	dermal (rat) LD50: >2000 mg/kg ^[1]	Skin (Rodent - ra	bbit): 1%/5D - Severe	
	Oral (Rat) LD50: 350 mg/kg ^[2]	Skin: adverse effe	ect observed (irritating) ^[1]	
	TOXICITY	IRRITATION		
	dermal (mouse) LD50: 1449 mg/kg ^[2]	Eye (Rodent - rat	obit): 5mg/30S - Mild	
	Oral (Rat) LD50: 900 mg/kg ^[2]	Eye: adverse effe	ect observed (irritating) ^[1]	
hydrochloric acid		Skin (Human): 49		
		Skin: adverse effe	ect observed (corrosive) ^[1]	
		Skin: adverse effe	ect observed (irritating) ^[1]	
Legend:	Nalue obtained from Europe ECHA Registered Substances - Acute to specified data extracted from RTECS - Register of Toxic Effect of chem	nical Substances	anica non manaractare a 355. Oness offici was	
ZINC CHLORIDE	Mutation DNA Damage Human. Equivocal tumorigenic agent by RTEC: The material may produce respiratory tract irritation, and result in dama The material may cause skin irritation after prolonged or repeated expo production of vesicles, scaling and thickening of the skin.	ige to the lung inclu		
HYDROCHLORIC ACID	No significant acute toxicological data identified in literature search. The substance is classified by IARC as Group 3: NOT classifiable as to its carcinogenicity to humans. Evidence of carcinogenicity may be inadequate or limited in animal test	ting.		
ZINC CHLORIDE & HYDROCHLORIC ACID	For acid mists, aerosols, vapours Test results suggest that eukaryotic cells are susceptible to genetic dan have not been examined in this respect. Mucous secretion may protect (which also protects the stomach lining from the hydrochloric acid secre The material may be irritating to the eye, with prolonged contact causin produce conjunctivitis. Asthma-like symptoms may continue for months or even years after ex condition known as reactive airways dysfunction syndrome (RADS) which compound. Main criteria for diagnosing RADS include the absence of pof persistent asthma-like symptoms within minutes to hours of a docum include a reversible airflow pattern on lung function tests, moderate to and the lack of minimal lymphocytic inflammation, without eosinophilia. disorder with rates related to the concentration of and duration of exposis a disorder that occurs as a result of exposure due to high concentration reversible after exposure ceases. The disorder is characterized by diffic	the cells of the ain- eted there). g inflammation. Re posure to the mate- ich can occur after- irevious airways dis- ented exposure to severe bronchial hy RADS (or asthma) sure to the irritating ions of irritating sub-	vay from direct exposure to inhaled acidic mists peated or prolonged exposure to irritants may rial ends. This may be due to a non-allergic exposure to high levels of highly irritating sease in a non-atopic individual, with sudden onset the irritant. Other criteria for diagnosis of RADS perreactivity on methacholine challenge testing, following an irritating inhalation is an infrequent substance. On the other hand, industrial bronchitis estance (often particles) and is completely	
Acute Toxicity	*	Carcinogenicity	×	
Skin Irritation/Corrosion	v	Reproductivity	×	
Serious Eye Damage/Irritation	✓ STOT - S	Single Exposure	×	
Respiratory or Skin sensitisation	X STOT - Rep	eated Exposure	×	
Mutagenicity	X As	spiration Hazard	×	

Legend:

Data either not available or does not fill the criteria for classification
 Data available to make classification

SECTION 12 Ecological information

Toxicity

	Endpoint	Test Duration (hr)	Species	Value	Source
CA 801 Soldering Fluid	Not Available	Not Available	Not Available	Not Available	Not Available
zinc chloride	Endpoint	Test Duration (hr)	Species	Value	Source
	BCF	1680h	Fish	58-116	7

Chemwatch: 20994 Page 3

CA 801 Soldering Fluid

Page 8 of 11 Issue Date: 23/12/2022
Print Date: 16/10/2024

	EC50	72h	Algae or other aquatic plants	0.011mg/L	4
		7211	Algae of other aquatic plants		4
	EC50	48h	Crustacea	0.011- 0.094mg/L	4
	LC50	96h	Fish	0.023- 0.031mg/l	4
	EC50	96h	Algae or other aquatic plants	0.026mg/L	4
	NOEC(ECx)	96h	Algae or other aquatic plants	0.05mg/L	1
	Endpoint	Test Duration (hr)	Species	Value	Source
	LC50		El-k	334.734mg/L	4
hydrochloric acid	LC50	96h	Fish	334.734IIIg/L	-
hydrochloric acid	EC50(ECx)	96h 9.33h	Fish	0.51mg/L	4

Very toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Prevent, by any means available, spillage from entering drains or water courses

DO NOT discharge into sewer or waterways

Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
zinc chloride	HIGH	HIGH
hydrochloric acid	LOW	LOW

Bioaccumulative potential

Ingredient	Bioaccumulation
zinc chloride	HIGH (BCF = 16000)
hydrochloric acid	LOW (LogKOW = 0.5392)

Mobility in soil

Version No. 6.1

Ingredient	Mobility
zinc chloride	LOW (Log KOC = 23.74)
hydrochloric acid	LOW (Log KOC = 14.3)

SECTION 13 Disposal considerations

Waste treatment methods

- ▶ Containers may still present a chemical hazard/ danger when empty.
- ▶ Return to supplier for reuse/ recycling if possible.

Otherwise:

- If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the
- same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.

 Where possible retain label warnings and SDS and observe all notices pertaining to the product.

Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws operating in their area. In some areas, certain wastes must be tracked.

A Hierarchy of Controls seems to be common - the user should investigate:

- Reduction
- ▶ Reuse
- Recycling
- Disposal (if all else fails)

Product / Packaging disposal

This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use. If it has been contaminated, it may be possible to reclaim the product by filtration, distillation or some other means. Shelf life considerations should also be applied in making decisions of this type. Note that properties of a material may change in use, and recycling or reuse may not always be appropriate.

- ▶ DO NOT allow wash water from cleaning or process equipment to enter drains.
- It may be necessary to collect all wash water for treatment before disposal.
- In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
- Where in doubt contact the responsible authority.
- Recycle wherever possible.
- Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.
- Treat and neutralise at an approved treatment plant. Treatment should involve: Neutralisation with soda-ash or soda-lime followed by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).
- Decontaminate empty containers with 5% aqueous sodium hydroxide or soda ash, followed by water. Observe all label safeguards until
 containers are cleaned and destroyed.

Ensure that the hazardous substance is disposed in accordance with the Hazardous Substances (Disposal) Notice 2017

Disposal Requirements

Packages that have been in direct contact with the hazardous substance must be only disposed if the hazardous substance was appropriately removed and cleaned out from the package. The package must be disposed according to the manufacturer's directions taking into account the material it is made of. Packages which hazardous content have been appropriately treated and removed may be recycled.

The hazardous substance must only be disposed if it has been treated by a method that changed the characteristics or composition of the substance and it is no longer hazardous.

Only dispose to the environment if a tolerable exposure limit has been set for the substance.

Only deposit the hazardous substance into or onto a landfill or sewage facility or incinerator, where the hazardous substance can be handled and treated appropriately.

Issue Date: 23/12/2022 Print Date: 16/10/2024

SECTION 14 Transport information

Labels Required Marine Pollutant

HAZCHEM

2X

Land transport (UN)

Land transport (ON)				
14.1. UN number or ID number	1760	1760		
14.2. UN proper shipping name	CORROSIVE LIQUID,	CORROSIVE LIQUID, N.O.S. (contains hydrochloric acid)		
14.3. Transport hazard class(es)	Class Subsidiary Hazard	8 Not Applicable		
14.4. Packing group	II	II .		
14.5. Environmental hazard	Environmentally hazardous			
14.6. Special precautions for user	Special provisions Limited quantity	274 1 L		

Air transport (ICAO-IATA / DGR)

All transport (ICAO-IATA / DOK	,			
14.1. UN number	1760			
14.2. UN proper shipping name	Corrosive liquid, n.o.s. * (contains hydrochloric acid)			
	ICAO/IATA Class	8		
14.3. Transport hazard class(es)	ICAO / IATA Subsidiary Hazard	Not Applicable		
5.135(05)	ERG Code	8L		
14.4. Packing group	II			
14.5. Environmental hazard	Environmentally hazardous			
	Special provisions		A3 A803	
	Cargo Only Packing Instructions		855	
	Cargo Only Maximum Qty / Pack		30 L	
14.6. Special precautions for user	Passenger and Cargo Packing Instructions		851	
usei	Passenger and Cargo Maximum Qty / Pack		1 L	
	Passenger and Cargo Limited Quantity Packing Instructions		Y840	
	Passenger and Cargo Limited Ma	aximum Qty / Pack	0.5 L	

Sea transport (IMDG-Code / GGVSee)

14.1. UN number	1760		
14.2. UN proper shipping name	CORROSIVE LIQUID, N.O.S. (contains hydrochloric acid)		
14.3. Transport hazard class(es)	IMDG Class IMDG Subsidiary Haza	8 ard Not Applicable	
14.4. Packing group	II .		
14.5 Environmental hazard	Marine Pollutant		
14.6. Special precautions for user	Special provisions	F-A , S-B 274 1 L	

14.7.1. Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

14.7.2. Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
zinc chloride	Not Available

Page **10** of **11**

CA 801 Soldering Fluid

Issue Date: 23/12/2022 Print Date: 16/10/2024

Product name	Group
hydrochloric acid	Not Available

14.7.3. Transport in bulk in accordance with the IGC Code

Product name	Ship Type
zinc chloride	Not Available
hydrochloric acid	Not Available

SECTION 15 Regulatory information

Safety, health and environmental regulations / legislation specific for the substance or mixture

This substance is to be managed using the conditions specified in an applicable Group Standard

HSR Number	Group Standard
HSR002610	Not Available

Please refer to Section 8 of the SDS for any applicable tolerable exposure limit or Section 12 for environmental exposure limit.

zinc chloride is found on the following regulatory lists

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

hydrochloric acid is found on the following regulatory lists

International Agency for Research on Cancer (IARC) - Agents Classified by the IARC Monographs - Not Classified as Carcinogenic

New Zealand Approved Hazardous Substances with controls

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals

New Zealand Hazardous Substances and New Organisms (HSNO) Act - Classification of Chemicals - Classification Data

New Zealand Inventory of Chemicals (NZIoC)

New Zealand Workplace Exposure Standards (WES)

Additional Regulatory Information

Not Applicable

Hazardous Substance Location

Subject to the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Quantity (Compliance Certificate)	Quantity (Compliance Certificate - Farms >4 ha)
6.1C	1000 kg or 1000 L	3500 kg or 3500 L
8.2A	50 kg or 50 L	500 kg or 500 L

Certified Handler

Subject to Part 4 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Class of substance	Quantities
Not Applicable	Not Applicable

Refer Group Standards for further information

Maximum quantities of certain hazardous substances permitted on passenger service vehicles

Subject to Regulation 13.14 of the Health and Safety at Work (Hazardous Substances) Regulations 2017.

Hazard Class	Gas (aggregate water capacity in mL)	Liquid (L)	Solid (kg)	Maximum quantity per package for each classification
6.1C	120	1	3	
8.2A	prohibited	prohibited	prohibited	

Tracking Requirements

Not Applicable

National Inventory Status

National Inventory Status				
National Inventory	Status			
Australia - AIIC / Australia Non- Industrial Use	Yes			
Canada - DSL	Yes			
Canada - NDSL	No (zinc chloride; hydrochloric acid)			
China - IECSC	Yes			
Europe - EINEC / ELINCS / NLP	Yes			
Japan - ENCS	Yes			
Korea - KECI	Yes			
New Zealand - NZIoC	Yes			
Philippines - PICCS	Yes			

Page 11 of 11 Issue Date: 23/12/2022 Print Date: 16/10/2024 CA 801 Soldering Fluid

National Inventory	Status	
USA - TSCA	All chemical substances in this product have been designated as TSCA Inventory 'Active'	
Taiwan - TCSI	Yes	
Mexico - INSQ	Yes	
Vietnam - NCI	Yes	
Russia - FBEPH	Yes	
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory. These ingredients may be exempt or will require registration.	

SECTION 16 Other information

Revision Date	23/12/2022
Initial Date	03/08/2004

SDS Version Summary

Version	Date of Update	Sections Updated
5.1	01/11/2019	One-off system update. NOTE: This may or may not change the GHS classification
6.1	23/12/2022	Classification review due to GHS Revision change.

Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be

Definitions and abbreviations

- ▶ PC TWA: Permissible Concentration-Time Weighted Average
- ▶ PC STEL: Permissible Concentration-Short Term Exposure Limit
- ▶ IARC: International Agency for Research on Cancel
- ▶ ACGIH: American Conference of Governmental Industrial Hygienists
- ▶ STEL: Short Term Exposure Limit
- ► TEEL: Temporary Emergency Exposure Limit.
- ▶ IDLH: Immediately Dangerous to Life or Health Concentrations
- ES: Exposure Standard
- OSF: Odour Safety Factor
- ▶ NOAEL: No Observed Adverse Effect Level
- LOAEL: Lowest Observed Adverse Effect Level
- ▶ TLV: Threshold Limit Value
- LOD: Limit Of Detection
- OTV: Odour Threshold Value
- ▶ BCF: BioConcentration Factors
- BEI: Biological Exposure Index
- DNEL: Derived No-Effect Level
- PNEC: Predicted no-effect concentration
- ▶ AIIC: Australian Inventory of Industrial Chemicals
- ▶ DSL: Domestic Substances List
- NDSL: Non-Domestic Substances List
- ▶ IECSC: Inventory of Existing Chemical Substance in China
- ▶ EINECS: European INventory of Existing Commercial chemical Substances
- ELINCS: European List of Notified Chemical Substances
- NLP: No-Longer Polymers
- ▶ ENCS: Existing and New Chemical Substances Inventory
- KECI: Korea Existing Chemicals Inventory
 NZIoC: New Zealand Inventory of Chemicals
- PICCS: Philippine Inventory of Chemicals and Chemical Substances
- ► TSCA: Toxic Substances Control Act
- ► TCSI: Taiwan Chemical Substance Inventory
- INSQ: Inventario Nacional de Sustancias Químicas
- NCI: National Chemical Inventory
- FBEPH: Russian Register of Potentially Hazardous Chemical and Biological Substances

This document is copyright.

Apart from any fair dealing for the purposes of private study, research, review or criticism, as permitted under the Copyright Act, no part may be reproduced by any process without written permission from CHEMWATCH.

TEL (+61 3) 9572 4700.