

Reduce install
time by 50%

Unique self adhesive
stretchable base

Compatible with concrete and
pressed metal tiles

RAPID FLASH®

Rapid Flash is an alternative to traditional lead & aluminium based boot flashings.

- Lead free
- Fully adhesive EPDM boot flashing
- Withstands high temperatures up to 115°C

Rapid Flash Range (Grey)

Part Number	Pipe Size mm	Base Size mm
DRF101GB	5 - 127	370 x 560
DRF103GB	50 - 170	370 X 560
DRF108GB	175 - 330	560 X 850

Same great material, also available as:

Fast Flash®

Fully adhesive lead-free roof flashing rolls.



Fast Flash Range (Grey)

Part Number	Width mm	Length
FFR5-280G	280	5m
FFR5-370G	370	5m
FFR5-560G	560	5m

Ask for it by name at your preferred
merchant supplier



DLM WALLACE
KIWI INGENUITY SINCE 1884

Proud Supplier of





Proudly Supplied By



RAPID FLASH®


Deks Rapid Flash is a complete flashing for weatherproofing pipe and flue penetrations through ALL tile roofs (concrete, clay, pressed metal tile, decramastic tile).

It consists of an EPDM Dektite flashing cone, with an integrated skirt made of Fastflash material


FEATURES:

- The base skirt is very malleable and stretchable like lead, allowing it to be easily formed to follow the contour of most tile profiles
- The fully adhesive base allows for a quick and easy install, without the requirement for silicone


Rapid Flash Range



5mm - 127mm



175mm - 330mm



50mm - 170mm

DEKS RAPID FLASH VS TILEFLASH ALUMINIUM

- The aluminium base of the Tileflash Aluminium is quite rigid and does not stretch, meaning it is difficult for it to form to tile profiles, and the finished aesthetics of the install can at times look poor.
- Deks Rapid Flash stretches, shapes and forms like lead, allowing for a quick and easy install, with a tidy looking finish

DEKS RAPID FLASH VS TILEFLASH LEAD

- Tileflash Lead is not compatible with modern zinc aluminium coated steel tiles
- Customers may desire a lead-free product

Part Number	Description	UOM	Pack QTY
DRF101GB	RAPIDFLASH BLK EPDM GRY FF 5-127MM (370x560MM)	EA	1
DRF103GB	RAPIDFLASH BLK EPDM GRY FF 50-170MM (370x560MM)	EA	1
DRF108GB	RAPIDFLASH BLK EPDM GRY FF 175-330MM (560x850MM)	EA	1