

# Dektite Premium


## The versatile solution

- ✓ Most extensive range of Dektites for flashing penetrations 0 - 510mm, available in black and grey EPDM and silicone red for high temperatures.
- ✓ Designed to enable practically any pipe flashing operation to be carried out within minutes, simple to install and very effective.
- ✓ The low profile cone not only looks good but provides a generous internal clearance, so even the steepest roofs are handled with ease.
- ✓ Suitable for flashing pipes that penetrate wall claddings.
- ✓ Can also be used to flash square penetrations. Just add 30% to the pipe diameter and trim the cone to suit.

- ✓ EPDM withstands temperatures from -50°C to 115°C and up to 150°C intermittently.
- ✓ Silicone withstands temperatures from -60°C to 200°C and up to 250°C intermittently.




## Installation Instructions:




### NOTE:


For more effective drainage, always fit the Dektite on the diamond or bias. Dektites are suitable for flashing pipes that penetrate wall claddings.




Cut a neat hole in roofing sheet with minimum clearance for pipe and insert pipe through hole. Trim the cone to suit pipe size using sharp tin snips. Where required, support cut sections of sheet with additional framing.




Slide Dektite flashing down over pipe. Lubricating the pipe with water allows the pipe to slide snugly into position.



Apply a neutral cure 100% silicone sealant (roof and gutter approved) to the underside of the Dektite by turning back the flexible flange.



Press base to the roof profile by hand, smooth out any awkward creases. Don't fully extend to allow for vibration.



Fasten using self drilling washered screws or sealed rivets. Fit fasteners progressively outward in opposing pairs to avoid gaps.

# Dektite Premium

The versatile solution

CODE: BLACK EPDM	CODE: GREY EPDM	CODE: RED SILICONE	BASE (MM)	PIPE (MM)	ROOF PITCH
DFE10MB			71 x 71	0-20	Up to 60° See foot note
DFE100B	DFE100G		100 x 100	0-35	
DFE100BS*		DFE200RES	100 x 100	0-35	
DFE101B	DFE101G		139 x 139	5-55	Up to 45° See foot note
DFE101BS*		DFE201RES	139 x 139	5-55	
DFE102BA	DFE102GA	DFE202REA	181 x 181	50-70	
DFE103B	DFE103G	DFE203RE	218 x 218	5-127	
DFE104B	DFE104G	DFE204RE	279 x 279	75-175	
DFE105B	DFE105G	DFE205RE	309 x 309	100-200	
DFE106B	DFE106G	DFE206RE	363 x 363	125-230	
DFE107B	DFE107G	DFE207RE	456 x 456	150-300	
DFE108B	DFE108G	DFE208RE	495 x 495	170-355	
DFE109B	DFE109G	DFE209RE	680 x 680	230-508	

\* DFE100BS and DFE101BS both have multiple cable nipples



## Can a Dektite flash a square pipe? **YES!**

100mm Round



Circumference = 314mm

100mm Square



Perimeter = 400mm

**Difference = Approx. 30%**

Therefore, to suit square pipes/stanchions add 30% to the diameter of the pipe and cut accordingly.

**100mm x 30% = 130mm  
to suit a square**

NOTE: Refer to page 7 for guide to Dektite square penetrations from 20mm - 125mm.